



Catalogues and Products > Riscaldamento > Termostati e Cronotermostati > **Adjustable Thermostat**

ADJUSTABLE THERMOSTAT

Capillary with liquid expansion probe

Product informations

Capillary thermostat equipped with liquid expansion probe with deviation contacts, suitable for automatic temperature regulation.

Pad-printed knob is also available, together with the support ferrule (SKU R03009).

Technical Features

ELECTRICAL CONTACT CAPACITY	NC 16(6) / A 250 VAC
CONTACTS	EXCHANGE
MAXIMUM HEAD TEMPERATURE	85°C
MINIMUM RADIUS OF CURVATURE OF THE CAPILLARY	5 MM
CONNECTION	THROUGH FASTON 6,3 X 0,8
ADJUSTABLE TEMPERATURE	0°C ÷ + 90°C
CAPILLARY LENGTH	<ul style="list-style-type: none"> • 1000 MM - SKU R03001 • 1500 MM (PVC COATED) - SKU R03000 • 1500 MM - SKU R03002
BULB DIMENSION	Ø 6,5 X 95 MM



Adjustable Thermostat

SKU	MODEL	PRICE
00000R03000	ADJUSTABLE THERMOSTAT - L. 1500 MM (PVC COATED) - INAIL CERTIFICATE	€20.2 VAT EXCLUDED
00000R03001	ADJUSTABLE THERMOSTAT - L. 1000 MM - TO BE COMBINED WITH KNOB AND FERRULE SKU R03009 - INAIL CERTIFICATE	€19.7 VAT EXCLUDED
00000R03009	ADJUSTMENT KNOB AND SUPPORT RING	€2.25 VAT EXCLUDED

