



ALUMINIUM THREADED SOLENOID VALVE FOR GAS

Normally open with manual reset without voltage, max. pressure 500 mbar

Product informations

Normally open manual reset solenoid valve for gas with manual reset without voltage.

The version for BIOGAS is also available on request (+ 10% on the cost).

Product features

- **FF threaded version**
- *it can only be reset manually and only when it is not electrically powered*
- equipped with VPI (Visual Position Indicator) for visual signaling of the position of the valve plug
- when the valve is closed, the red band normally hidden by the reset knob is visible

Technical Features

USE	NOT AGGRESSIVE GASES OF THE THREE FAMILIES (DRY GASES)
ROOM TEMPERATURE	- 20°C ÷ + 60°C
SUPPLY VOLTAGES	230 V 50 - 60 HZ (ONLY SINGLE-PHASE, THE DEVICE DOES NOT WORK IF POWERED WITH THREE-PHASE VOLTAGE)
ELECTRICAL WIRING	STRAIN RELIEF M20 X 1.5
ABSORBED POWER	230 V = 7/8 VA
MAXIMUM WORKING PRESSURE	500 MBAR
CLOSING TIME	< 1 S



Aluminium Threaded Solenoid Valve for Gas

DEGREE OF PROTECTION	IP65 (PROTECTED AGAINST JETS OF WATER PUMPED FROM ANY DIRECTION AND COMPLETELY HERMETIC AGAINST DUST AND FUMES)
MATERIALS	ALUMINUM
MECHANICAL STRENGTH	GROUP 2
CONNECTIONS	3/4" FF - 1" 1/4 FF - 1" FF - 1" 1/2 FF - 2" FF
COMPLIANCE	<ul style="list-style-type: none"> • EMC DIRECTIVE 2014/30/EU • LVD DIRECTIVE 2014/35/EU • ROHS II DIRECTIVE 2011/65/EU

SKU	MODEL	PRICE
00000050332	ALUMINUM SOLENOID VALVE FOR GAS - 3/4" FF - 500 MBAR	€113.75 VAT EXCLUDED
00000050333	ALUMINUM SOLENOID VALVE FOR GAS - 1" FF - 500 MBAR	€113.75 VAT EXCLUDED
00000050334	ALUMINUM SOLENOID VALVE FOR GAS - 1" 1/4 FF - 500 MBAR	€148.25 VAT EXCLUDED
00000050335	ALUMINUM SOLENOID VALVE FOR GAS - 1" 1/2 FF - 500 MBAR	€148.25 VAT EXCLUDED
00000050336	ALUMINUM SOLENOID VALVE FOR GAS - 2" FF - 500 MBAR	€174.3 VAT EXCLUDED

