



Catalogues and Products > Air-Conditioning > Staffe > **Anchor**

## ANCHOR

With hex head screw

### Product informations

Universal anchor for fastenings on all types of masonry, plasterboard and concrete.

### Product features

- particularly suitable in perforated and hollow walls
- thanks to its special shaping, allows expansion in 6 different directions for consistently effective anchorages on all types of masonry
- equipped with a dynamic collar that allows both a flush-wall installation and a through-wall installation
- anti-rotation mechanisms for perfect functionality during tightening

### Installation

For proper installation of the anchor, drill the hole perpendicular to the support with a drill bit of the appropriate diameter. The hole should be cleaned of drilling dust before applying the anchor; it is recommended not to use roto-percussion when drilling the hole on a wall with perforated brick so as not to break the internal bulkheads. Insert the anchor and carry out the desired installation.

### Technical Features



**Anchor**

ANCHOR MATERIAL	SCREW MATERIAL	MINIMUM DRILLING DEPTH	MAXIMUM FIXABLE THICKNESS	A	S	H	R
POLYAMIDE 6	7-8 M ELECTROGALVANIZED TREATED STEEL	65 MM	15 MM	8,4X16X1,6 MM	50 MM	7X70 MM	10 MM

SKU	MODEL	PRICE
00000011885	ANCHOR WITH HEX HEAD SCREW	€1.9 VAT EXCLUDED

