



BLUE KIT BASIC 3.0

The complete boiler-saver kit

Product informations

- **BLUE KIT BASIC 3.0** consists of the magnetic filter *DSBLUE.PL* (SKU 70049), the polyphosphate dispenser *Dosablue ONE* (SKU 70874) and the *Neutral Acid Water 35K* neutralizing cartridge (SKU 70894).
- **BLUE KIT BASIC 3.1** consists of the *MINI DSBLUE.PL* magnetic defanger (SKU 70044), *Dosablue ONE* polyphosphate dispenser (SKU 70874), and *Neutral Acid Water 35K* neutralizing cartridge (SKU 70894).
- **BLUE KIT BASIC 3.2** consists of the *MINI DSBLUE.PL* magnetic defuser (SKU 70044), the *Dosablue ONE* polyphosphate dispenser (SKU 70874), and the *Neutralizing Cartridge Compact Neutral Acid Water* (SKU 70892).
- **BLUE KIT BASIC 3.3** consists of the *PLASTICMAG.PL* (SKU 70038), the *Dosablue ONE* polyphosphate dispenser (SKU 70874), and the *Neutralizing Cartridge Compact Neutral Acid Water* (SKU 70892)

Technical Features

SKU 70874	
90° CONNECTIONS	IN/OUT 1/2" MOBILE
MAX FLOW RATE	1,5 M ³ /H
MAX PRESSURE	3,5 BAR
WORKING TEMPERATURE	0°C - 45°C
RECHARGE AUTONOMY	12 - 15 M ³
PRESSURE DROP	0,2 BAR
VASE MATERIAL	SAN



<i>SKU 70049</i>	
<i>CHEMICAL COMPATIBILITY</i>	WATER / WATER AND GLYCOL
<i>MAX INLET PRESSURE</i>	3 BAR
<i>WORKING TEMPERATURE</i>	0 ÷ 90°C
<i>DEGREE OF FILTRATION</i>	800 μM
<i>THREADED CONNECTIONS</i>	G 3/4" FF UNI-EN-ISO 228
<i>KV (RANGE WITH DP 1 BAR)</i>	5,4 M ³ /H
<i>MAGNETIC FIELD INTENSITY</i>	11000 GAUSS

<i>SKU 70894</i>	
<i>VALID FOR BOILERS UP TO 35 KW</i>	
<i>LENGTH</i>	220 MM
<i>DIAMETER</i>	47 MM
<i>MAX PRESSURE</i>	0,5 BAR
<i>MAXIMUM TEMPERATURE</i>	60°C
<i>MAX CAPACITY</i>	8 L/H
<i>UNIT MATERIAL</i>	PP
<i>HOSE HOLDER MATERIAL</i>	PP
<i>MATERIAL FIXING SYSTEM</i>	PP
<i>NEUTRALIZING CHARGE IN CALCIUM CARBONATE (CaCO₃)</i>	
<i>EPDM HYDRAULIC SEALS</i>	


Blue Kit Basic 3.0

SKU 70894	
ACCESSORIES	<ul style="list-style-type: none"> • PAIR OF 3/4" STRAIGHT HOSE CONNECTORS • FIXING CLIP WITH Ø 50 MM SCREWS

SKU 70044	
CHEMICAL COMPATIBILITY	WATER / WATER AND GLYCOL
MAX INLET PRESSURE	3 BAR
WORKING TEMPERATURE	0 ÷ 90°C
DEGREE OF FILTRATION	800 μM
THREADED CONNECTIONS	G 3/4" M/F UNI-EN ISO 228
KV (RANGE WITH DP 1 BAR)	4,45 M ³ /H
MAGNETIC FIELD INTENSITY	7000 GAUSS
DIMENSIONS	58X120X90 MM (AXBXC)
UNIT	CHROME-PLATED BRASS
CONNECTIONS	CHROME-PLATED BRASS FG 3/4" / 3/4" M
BALL VALVE	CHROME-PLATED BRASS
FILTERING ELEMENT	AISI 304 STAINLESS STEEL MESH
MAGNET	RUTHENIUM
SEALS	EPDM

SKU 70892	
MAXIMUM OPERATING PRESSURE	0,5 BAR


Blue Kit Basic 3.0

<i>SKU 70892</i>	
MAXIMUM OPERATING TEMPERATURE	45°C
FLOW RATE	3 L/H
MATERIALS	<ul style="list-style-type: none"> • BODY: PP • HOSE CONNECTOR: PP • FASTENING SYSTEM: PP • NEUTRALIZING CHARGE: CALCIUM CARBONATE (CaCO₃) • HYDRAULIC SEALS: NBR
CONNECTIONS	3/4"
DIMENSIONS	LENGTH 238 MM

<i>SKU 70038</i>	
CHEMICAL COMPATIBILITY	WATER / WATER AND GLYCOL
MAX INLET PRESSURE	3 BAR
WORKING TEMPERATURE	0 ÷ 90°C
DEGREE OF FILTRATION	G 3/4" M/F UNI-EN ISO 228
KV (RANGE WITH DP 1 BAR)	5,4 M ³ /H
MAGNETIC FIELD INTENSITY	9000 GAUSS
CONNECTIONS	3/4"
DIMENSIONS	92X62X110X195 MM (AXBXCXD)
MATERIAL	<ul style="list-style-type: none"> • BODY: POLIPROPILENE +30% FV • TAPS AND CONNECTIONS: BRASS CW 617N UNI EN 12165 NICKEL-PLATED • DIFFUSER ELEMENT: POLYPROPYLENE +30% PV • MAGNET: NEODYMIUM 9000 GAUSS



Blue Kit Basic 3.0

SKU	MODEL	PRICE
00000070074	BLUE-KIT BASIC 3.0	€123.6 VAT EXCLUDED
00000070061	BLUE-KIT BASIC 3.1	€129.9 VAT EXCLUDED
00000070062	BLUE-KIT BASIC 3.2	€129.9 VAT EXCLUDED
00000070063	BLUE-KIT BASIC 3.3	ON REQUEST
CMP00070062	COMPONENTI PER 70062	ON REQUEST

