



BOXED IMMERSION BITHERMOSTAT

Equipped With liquid expansion probe

Product informations

Double boxed immersion thermostat, with liquid expansion probes, unipolar, temperature regulator and temperature limiter, fail-safe for capillary breakage, complete with watertight protection sheath. Particularly suitable for appliances where temperature control and safety is required.

Technical Features

<i>ELECTRICAL CONTACT CAPACITY</i>	10 (2,5) A / 250 VAC
<i>CONTACT</i>	INTERRUPTED DUE TO TEMPERATURE INCREASE OR EXCHANGE
<i>MAXIMUM HEAD TEMPERATURE</i>	80°C
<i>MAXIMUM BULB TEMPERATURE</i>	125°C
<i>TEMPERATURE RANGE</i>	0°C ÷ 90°C - SAFETY 100°C
<i>THERMAL GRADIENT</i>	1°K/MIN



Boxed Immersion Bithermostat

DEGREE OF PROTECTION	IP40 (NOT PROTECTED AGAINST THE INGRESS OF LIQUIDS, BUT PROTECTED AGAINST THE INGRESS OF SOLID OBJECTS LARGER THAN 1 MM)
SHEATH CONNECTION	G1/2"
SHEATH LENGTH	100 MM

SKU	MODEL	PRICE
00000R02909	REPLACEMENT COCKPIT FOR BITHERMOSTAT MOD. TLSC	€25.95 VAT EXCLUDED
00000R03097	BOXED IMMERSION BITHERMOSTAT WITH LIQUID EXPANSION PROBE - 0°C ÷ 90°C	€97.65 VAT EXCLUDED

