



CENTERING COLLAR

Device for the support of the flue system

Product informations

Centering collar, to be used when it is necessary to support the flue system in narrow shafts and to keep it at a due distance from the walls; *to be used compulsorily every 2 meters* to ensure the integrity of the duct and its functions even at high temperatures.

Product features

- made in diameters: Ø 50 mm - Ø 60 mm - Ø 80 mm - Ø 100 mm - Ø 125 mm - Ø 160 mm - Ø 200 mm
- finished in RAL 9010 color

Technical Features

DESIGNATION	T120 P1 W 2 O00 LI E U
MATERIAL	PP (THERMOPLASTIC POLYMER)
OPERATING TEMPERATURE	CONTINUES UP TO 120°C

SKU	CENTRAL DIAMETER	A	B
51327	Ø 50 MM	170	25
51328	Ø 60 MM	170	25



Centering Collar

SKU	CENTRAL DIAMETER	A	B
51330	Ø 80 MM	170	25
51739	Ø 100 MM	170	25
51329	Ø 125 MM	170	25
51389	Ø 160 MM	170	25
51396	Ø 200 MM	170	25

SKU	MODEL	PRICE
00000051327	CENTERING COLLAR - Ø 50 MM	€6.95 VAT EXCLUDED
00000051328	CENTERING COLLAR - Ø 60 MM	€6.95 VAT EXCLUDED
00000051329	CENTERING COLLAR - Ø 80 MM	€6.95 VAT EXCLUDED
00000051330	CENTERING COLLAR - Ø 100 MM	€6.95 VAT EXCLUDED
00000051739	CENTERING COLLAR - Ø 200 MM	€8.2 VAT EXCLUDED
00000051389	CENTERING COLLAR - Ø 125 MM	€7.2 VAT EXCLUDED
00000051396	CENTERING COLLAR - Ø 160 MM	€7.9 VAT EXCLUDED

