



Daily and/or Weekly Digital Analog Chronothermostat

Catalogues and Products > Heating > Thermostats and Chronothermostats > **Daily and/or Weekly Digital Analog Chronothermostat**

DAILY AND/OR WEEKLY DIGITAL ANALOG CHRONOTHERMOSTAT

Model CR308/G and CR309/S

Product informations

Battery powered 3V analog digital chronothermostat, available with *daily programming (Mod. CR308/G)* and/or *weekly programming (Mod. CR309/S)*.

Product features

- display Lcd 2" 2/3
- ON/OFF operation with adjustable differential from 0.3°C / 0.5°C / 0.7°C / 0.9°C or modulating with control period 7/10/15/20 min
- temperature set adjustment shown on the display
- 2 temperature levels + antifreeze fixed at 5°C
- minimum programming of 30 minutes
- permanent manual operation
- temperature lock
- telephone command input

FUNCTIONS OF BUTTONS AND SYMBOLS

FUNCTIONS OF BUTTONS AND SYMBOLS	
1	SETTING BUTTON: HOURS-MINUTES OR ROOM TEMPERATURE DISPLAY
2	SWITCH - TYPE OF OPERATING MODE
3	BATTERY COMPARTMENT
4	"TAPPET" KEY



Daily and/or Weekly Digital Analog Chronothermostat

<i>FUNCTIONS OF BUTTONS AND SYMBOLS</i>	
5	ADJUSTMENT KNOB "COMFORT SET" TEMPERATURE
6	"SET REDUCTION" ADJUSTMENT KNOB (SAVING)
7	DAY SETTING BUTTON (<i>ONLY WEEKLY MODEL</i>)
8	DISPLAY OF OPERATION IN PROGRESS
9	ACTIVATION VIA WEEKLY PROGRAMMER (WITH FLASHING INDICATOR)
10	VISUALIZATION OF THE INSERTED PROGRAM: <ul style="list-style-type: none"> • INDEX ON = COMFORT • INDEX OFF = REDUCTION
11	BATTERY INDICATOR: <ul style="list-style-type: none"> • ALMOST FLAT (<i>BLINKING</i>) • FLAT (<i>CONSTANTLY LIT</i>)
12	USER STATUS INDICATOR: <ul style="list-style-type: none"> • BLINKING = RELAY ON • OFF = RELAY OFF
13	FLASHING CURRENT 1/2H INDEX
14	CURRENT HOUR OR ROOM TEMPERATURE DETECTED / TEMPERATURE SETTING
15	"TAPPET" KEY
16	DAY (<i>ONLY WEEKLY MODEL</i>)
17	RESET

Technical Features



Daily and/or Weekly Digital Analog Chronothermostat

POWER SUPPLY	TWO 1,5 V AA ALKALINE BATTERIES (DURACELL OR ENERGIZER RECOMMENDED)
AUTONOMY	2 YEARS
TYPE OF DISCONNECTION AND DEVICE	1/B/U ELECTRONIC
SOFTWARE	CLASS A
RATED IMPULSE VOLTAGE	4 KV
TYPE OF OUTPUT	RELAY WITH POTENTIAL FREE NO/COM/NC CHANGEOVER CONTACT - MAX 5(3) A/250 VAC
INPUT FOR PHONE PROGRAMMER	FOR POTENTIAL FREE NO CONTACT
TYPE OF INSULATION	CLASS II
DEGREE OF PROTECTION	IP30 (NOT PROTECTED AGAINST THE INGRESS OF LIQUIDS, BUT PROTECTED AGAINST THE INGRESS OF SOLID OBJECTS LARGER THAN 2,5 MM)
PROGRAMMABLE INDICES ON THE CLOCK	48
ANTIFREEZE TEMPERATURE	+ 5°C
THERMAL GRADIENT	MAX 1K / 15 MIN
CLOCK ACCURACY	± 1 SEC/GG
REGULATION RANGE	5°C ÷ 37.7°C
DIMENSIONS	121,5 X 31,5 X 82 MM (WXDXH)
COLOR	WHITE



**Daily and/or Weekly Digital Analog
Chronothermostat**

SKU	MODEL	PRICE
00000080530	DAILY ANALOG DIGITAL CHRONOTHERMOSTAT - MOD. CR308/G	€110.0 VAT EXCLUDED
00000080532	WEEKLY DIGITAL ANALOG CHRONOTHERMOSTAT - MOD. CR309/S	€113.1 VAT EXCLUDED

