



Catalogues and Products > Riscaldamento > Centraline, Manichette e Raccorderia > **Flexible Hoses for Place Group**

FLEXIBLE HOSES FOR PLACE GROUP

Version completely in stainless steel

Product informations

Flexible hoses for place group control entirely in stainless steel, with external coating in white PVC against saline oxidation.

Technical Features

<i>OPERATING PRESSURE</i>	20 BAR
<i>WORKING FLUID</i>	COMBUSTIBLE GASES
<i>BURST PRESSURE</i>	80 BAR
<i>MAX TEMPERATURE</i>	100°C
<i>BENDING RADIUS (MINIMUM PERMISSIBLE IN STATIC CONDITIONS RP)</i>	32 MM
<i>RADIUS OF CURVATURE (MINIMUM FOR RC CYCLIC MOVEMENTS)</i>	130 MM
<i>LENGTH</i>	60 CM - 120 CM
<i>CONNECTION</i>	FF SX CH 25



Flexible Hoses for Place Group

SKU	MODEL	PRICE
00000006403	FLEXIBLE HOSE FOR PLACE GROUP - 120 CM - FF CONNECTION LEFT	€64.25 VAT EXCLUDED
00000006407	FLEXIBLE HOSE FOR PLACE GROUP - 60 CM - FF CONNECTION LEFT	€49.9 VAT EXCLUDED

