



GAS LEAK DETECTOR

Model INC 95

Product informations

INC 95, the detector complete with power supply and actuator device without the need to install additional accessories, characterized by the high reliability, practicality and versatility of a universal recessed system; it can be inserted in the frames and plates of the main manufacturers, without the need for additional external adapters.

Product features

- high selectivity, free from false alarms
- sensor end of life indication
- integrated microcontroller
- sensor failure control
- actuator relay to control external accessories
- compatible with frames: AVE, BTICINO Living, GEWISS Playbus, VIMAR Idea

Technical Features

GAS DETECTED	<ul style="list-style-type: none"> • CH₄ - SKU 503428 • GPL - SKU 503429
POWER SUPPLY	230 VAC 50 - 60 HZ (± 10%)
ABSORPTION	3.3 VA (STAND-BY)
ACUSTIC SIGNAL	BUZZER > 85 DBA A 1 METER
ALARM RELAY	1, HERMETIC 250 VAC 5 A (NO / C / NC)


Gas Leak Detector

OPERATING TEMPERATURE	- 10°C ÷ + 40°C
RELATIVE HUMIDITY	30 ÷ 90 % RH WITHOUT CONDENSATION
DEGREE OF PROTECTION	IP40 (NOT PROTECTED AGAINST THE INGRESS OF LIQUIDS, HOWEVER PROTECTED AGAINST THE INGRESS OF SOLID OBJECTS LARGER THAN 1 MM)
LED INDICATORS	<ul style="list-style-type: none"> • GREEN: SIGNAL PRESENCE • YELLOW: FAULT SIGNAL • RED: ALARM
CONTAINER	PC/ABS UL94-VO SELF-EXTINGUISHING
ASSEMBLY	RECESSED
PREHEATING TIME	< 30 SECONDS
RESPONSE TIME	< 15 SECONDS
TYPE OF SENSOR	CATALYTIC
ALARM THRESHOLD	10% L.I.E.
INTERFACE	1 TASTO (RESET AND TEST OF THE DETECTOR WITH COUNTING OF THE YEARS OF LIFE OF THE SENSOR)
DIMENSIONS	74,5 X 44,5 X 57 MM (LXWXD)

SKU	MODEL	PRICE
00000503428	GAS LEAK DETECTOR MOD. INC 95 CH4	€260.3 VAT EXCLUDED
00000503429	GAS LEAK DETECTOR MOD. INC 95 GPL	€260.3 VAT EXCLUDED



Gas Leak Detector

