



Catalogues and Products > Heating > Gruppi di Riduzione Gpl > **Double Line Reduction Group for LPG**

DOUBLE LINE REDUCTION GROUP FOR LPG

Version 1ST Stage with/without OPSO shut-off valve, flow rate 500 kg/h

Product informations

Double line reduction group for LPG version **1ST Stage** with/without OPSO shut-off valve, consisting of two identical lines, one service and one relief line.

STRUCTURE OF THE REDUCTION GROUP	
1	BALL VALVE
2	REGULATOR
3	BUTTERFLY VALVE
4	CONDENSATE TANK
5	PRESSURE GAUGE
6	DISCHARGE BALL VALVE
7	RELIEF VALVE
8	NEEDLE TAP
9	SQUARE BALL VALVE
10	MAX PRESSURE SHUT-OFF VALVE - <i>PRESENT ONLY IN SKU 13042</i>

Technical Features

FLOW RATE	500 KG/H
-----------	----------



Double Line Reduction Group for LPG

INLET CONNECTION	DN 40
OUTLET CONNECTION	DN 65
INLET PRESSURE	2 ÷ 18 BAR
OUTPUT PRESSURE	0.5 BAR
TYPE OF REGULATOR	ALFA 40 MODEL
GAUGE TYPE	Ø 60 - 1/4" RADIAL CONNECTION
BUTTERFLY VALVE	DN 65 - PN 16
DISCHARGE BALL VALVE	1/4" CONNECTION - PN 16
SAFETY VALVE CONNECTION	1/4"
SQUARE BALL VALVE	1/2" - PN 16 CONNECTION
BALL VALVE	DN 40 - PN 40
CONDENSATE TANK DIAMETER	Ø 6"
MAX PRESSURE SHUT-OFF VALVE	OPSO - <i>PRESENT ONLY IN SKU 13042</i>
NEEDLE TAP	1/4" - PN 40

SKU	MODEL	PRICE
00000013041	DOUBLE LINE REDUCING GROUP FOR LPG 1 ST STAGE - FLOW RATE 500 KG/H	€7372.0 VAT EXCLUDED
00000013042	DOUBLE LINE REDUCING GROUP FOR LPG 1 ST STAGE - FLOW RATE 500 KG/H - WITH OPSO SHUT-OFF VALVE	€8436.0 VAT EXCLUDED



Double Line Reduction Group for LPG

