



DOUBLE LINE REDUCTION GROUP FOR LPG

Version 2ND Stage with/without OPSO shut-off valve, flow rate 200 kg/h

Product informations

Double line reduction group for LPG version **2ND Stage** with/without OPSO shut-off valve, consisting of two identical lines, one service and one relief line.

STRUCTURE OF THE REDUCTION GROUP	
1	BALL VALVE
2	REGULATOR
3	BUTTERFLY VALVE
4	CONDENSATE TANK
5	PRESSURE GAUGE
6	DISCHARGE BALL VALVE
7	NEEDLE TAP
8	MAX PRESSURE SHUT-OFF VALVE - <i>PRESENT ONLY IN SKU 13049</i>

Technical Features

FLOW RATE	200 KG/H
INLET CONNECTION	DN 40
OUTLET CONNECTION	DN 50



Double Line Reduction Group for LPG

<i>INLET PRESSURE</i>	0,5 ÷ 2 BAR
<i>OUTPUT PRESSURE</i>	ON REQUEST
<i>TYPE OF REGULATOR</i>	ALFA 35 MODEL WITH RELIEF VALVE
<i>TYPE OF PRESSURE GAUGE</i>	Ø 60 - 1/4" RADIAL CONNECTION
<i>BUTTERFLY VALVE</i>	DN 50 - PN 16
<i>DISCHARGE BALL VALVE</i>	1/2" CONNECTION - PN 16
<i>CONDENSATE TANK DIAMETER</i>	Ø 4"
<i>MAX PRESSURE SHUT-OFF VALVE</i>	OPSO - <i>PRESENT ONLY IN SKU 13049</i>
<i>NEEDLE TAP</i>	1/4" - PN 40

SKU	MODEL	PRICE
00000013048	DOUBLE LINE REDUCING GROUP FOR LPG 2ND STAGE - FLOW RATE 200 KG/H	€4218.0 VAT EXCLUDED
00000013049	DOUBLE LINE REDUCING GROUP FOR LPG 2ND STAGE - FLOW RATE 200 KG/H - WITH OPSO SHUT-OFF VALVE	€5130.0 VAT EXCLUDED

