



Horizontal Regulator Kit for Domestic Use

Catalogues and Products > Riscaldamento > Regolatori gpl per applicazioni ad uso domestico, alta e bassa pressione > **Horizontal Regulator Kit for Domestic Use**

HORIZONTAL REGULATOR KIT FOR DOMESTIC USE

Fixed setting model, flow rate 1,1 kg/h

Product informations

Regulator kit for domestic use, equipped with 1,5 m LPG pipe and accessories.

Technical Features

TYPES OF GAS	BUTANE - LPG
FLOW RATE	1,1 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	<ul style="list-style-type: none"> • LPG: 0,3 ÷ 16 BAR • BUTANE: 0,3 ÷ 7,5 BAR
OUTLET PRESSURE	<ul style="list-style-type: none"> • LPG: 37 MBAR • BUTANE: 29 MBAR
LOAD LOSS	ΔP2
CONNECTIONS	<ul style="list-style-type: none"> • INPUT: CH25 NUT • OUTLET: HOSE NOZZLE
Ø MAX DOWNSTREAM CONNECTING PIPE	8 MM

SKU	MODEL	PRICE
0000000450K	REGULATOR KIT T.F. FOR DOMESTIC USE - FIXED SETTING - FLOW RATE 1,1 KG/H	€14.7 VAT EXCLUDED



Horizontal Regulator Kit for Domestic Use

