



Catalogues and Products > Air-Conditioning > Staffe > **Insulating Fixing**

INSULATING FIXING

For walls with coat insulation

Product informations

Professional fixing ideal fixing for blocking external units or suspended loads on buildings insulated with thermal insulation from 80 to 160 mm.

Product features

- fiberglass-reinforced nylon insulation body, has its inside a barrier that interrupts thermal bridging by preventing condensation and drip points inside the masonry
- ideal for securing climate machines and suspended loads in general in buildings insulated with insulation
- suitable for different types of masonry, such as concrete, solid brick masonry or perforated masonry (when used with TCH, PE165 and THC PE300 injection resins)
- equipped with TOP ultra-performance meshed sleeve with anti-rotation and anti-unthreading fins, M12x200 threaded rod, plastic support washer, lock nut and M10x25 INOX fastening bolt
- *for the hanging fixing of air conditioning unit, it is always recommended to use 4 fixings: 2 on the crossbeam and 2 on the vertical metal struts*

Technical Features

THREADED ROD MATERIAL	STEEL 4.8 EN ISO 898-1 ELECTROLYTIC GALVANIZING 7-8 µM
MESHED COMPASS MATERIAL	PE POLYETHYLENE
WASHER MATERIAL	PP POLYPROPYLENE



Insulating Fixing

BOLT MATERIAL	STAINLESS STEEL AISI 304 - EN 10088
CIRCUIT BREAKER MATERIAL	PA6 GLASS FIBER FILLED POLYAMIDE
TYPE OF COATS	80-160 MM
MINIMUM DRILLING DEPTH	180 MM
A	40 MM
B	76 MM
C	M10
D	M12
E	M12
F	200 MM
G	40 MM
H	100 MM
I	M12
R	16 MM

SKU	MODEL	PRICE
00000011884	INSULATING FIXING FOR WALLS WITH COAT INSULATION	€67.65 VAT EXCLUDED



Insulating Fixing

