



Catalogues and Products > Riscaldamento > Solare Termico > Integration Kit

INTEGRATION KIT

Integration kit between solar panel and boiler for the production of domestic hot water

Product informations

Kit consisting of a diverter valve and an adjustable mixing valve, designed to be used in cases where it is necessary to integrate a solar storage tank with a combustion heating system with storage boiler. The collector placed between the two valves allows a compact, versatile and reliable integration of the solar system, the anti-scald safety function automatically blocks the supply of potentially scalding hot water in case of sudden absence of pressure in the cold water connection; even in the event of a sudden lack of hot water, the device will interrupt the passage of cold water and therefore the outlet flow, thus avoiding unpleasant thermal shocks.

The thermal insulation shell is available on request.

How does it work

If the fluid temperature is higher than the set value, the diverting valve has the task of diverting the water coming from the solar storage directly to the adjustable mixing valve and therefore to the utilities, at the desired temperature; when the temperature of the water coming from the storage falls below the deviation value, the diverting valve directs the water towards the boiler, which is activated by increasing its temperature. The water leaving the boiler circulates in the mixing valve which regulates the temperature before being conveyed to the users.

Technical Features



Viale L. Da Zara 10 35020 Albignasego Padova – Italy P.IVA: 03859580288 Tel: +39 049 8625910 Mail: info@tecnogas.net Page: 1



Integration Kit



MAXIMUM PERMISSIBLE PRESSURE	10 BAR
MAXIMUM WORKING PRESSURE	5 BAR
MINIMUM CAPACITY (FOR CORRECT OPERATION)	9 L/MIN
MAXIMUM INLET TEMPERATURE	100°C
REGULATION RANGE	30°C ÷ 65°C
PRECISION	± 2°C
FLOW COEFFICIENT	1,1 KV
CONNECTION TO THE PIPE	THREAD ACCORDING TO ISO 228/1
COMPATIBLE FLUIDS	WATER
MATERIALS	 BODY: UNI EN 12165 CW 602 N (DZR) CHROMED BRASS WITH EN12540 ELECTROLYTIC COATING HANDLE: PBT INTERNAL ORGANS ACCORDING TO UNI EN 12164 CW 617 N - UDEL GF-120 NT SPRINGS: AISI 302 STAINLESS STEEL SEALING ELEMENTS: EPDM THERMOSENSITIVE ELEMENT: WAX
CONNECTIONS	1/2" MM



Viale L. Da Zara 10 35020 Albignasego Padova – Italy P.IVA: 03859580288 Tel: +39 049 8625910 Mail: info@tecnogas.net Page: 2



Integration Kit



SKU	MODEL	PRICE
00000070962	INTEGRATION KIT - 1/2" MM	€491.2 VAT EXCLUDED





Viale L. Da Zara 10 35020 Albignasego <u>Pado</u>va – Italy P.IVA: 03859580288 Tel: +39 049 8625910 Mail: info@tecnogas.net Page: 3