



MANIFOLD IN PE BILATERAL

End-of-line transition bilateral manifold in PE for the adduction of fluids

Product informations

Threaded PE (polyethylene) manifolds designed for the connection of water meters in residential areas. This product is also non-toxic, anti-odour and offers maximum resistance to aggression from chemical agents.

Product features

- ideal for multi-user houses
- unlimited number of derivations thanks to the possibility of joining several modules (on demand)
- mechanical, impact and aging resistance
- there is no lead in contact with drinking water

Technical Features

MAX PRESSURE	16 BAR
TEMPERATURE RANGE	- 30°C ÷ + 60°C
MATERIAL	<ul style="list-style-type: none">• PE100 SDR11 UNI EN 12201-2• INSERT AND NUT IN BRASS• WIRE TRANSITION ADAPTER PE/BRASS MALE
CONNECTION	3/4" O 1/2"
POSITIONS	4 - 8 POSITIONS



Manifold in PE Bilateral

REFERENCE STANDARDS	<ul style="list-style-type: none"> • DM 174/2014: REGULATION CONCERNING THE MATERIALS AND OBJECTS THAT CAN BE USED IN FIXED PLANTS FOR THE COLLECTION, TREATMENT, ADDUCTION AND DISTRIBUTION OF WATER INTENDED FOR HUMAN CONSUMPTION. (GU GENERAL SERIES N.166 OF 17-07-2004) • UNI EN 12201-3:2013: PLASTICS PIPING SYSTEMS FOR WATER DISTRIBUTION, AND FOR PRESSURIZED WASTE AND SEWER - POLYETHYLENE (PE) - PART 3: FITTINGS. • UNI 9736:2014: FITTINGS MANUFACTURED WITH MIXED METAL-POLYETHYLENE JOINT FOR USE IN PIPELINES FOR COMBUSTIBLE GASES, WATER AND OTHER PRESSURIZED FLUIDS AND METAL-PROPYLENE FOR USE IN PIPELINES FOR WATER AND OTHER PRESSURIZED FLUIDS.
----------------------------	---

SKU	MODEL	PRICE
B18TF321204		ON REQUEST
B18TF321208		ON REQUEST
B18TF323404		ON REQUEST
B18TF323408		ON REQUEST
B18TF503404		ON REQUEST
B18TF503408		ON REQUEST
B18TF633404		€242.55 VAT EXCLUDED
B18TF633408		€386.3 VAT EXCLUDED



U:unilaterale / unilaterale B:bilaterale / bilaterale
 interasse / interasse base.....
 ø saldare / di transizione: unilaterale / bilaterale.....
 Fin: fine linea / end line P:prolunga / extension.....
 Ø collettore mm / Ø manifold mm.....
 Ø stacchi mm / Ø disengagements mm.....
 pt. allacci / n° connections.....

U:18 S:F:32:34:02
 B:18 T:F:50:34:08