



MANUAL RESET SOLENOID VALVE FOR GAS

Normally open with manual closing safety button, max. pressure 500 mbar

Product informations

Manual reset solenoid valve for gas, normally open with manually closed safety button.

Product features

- *it can only be reset manually and only when it is not electrically powered*
- equipped with VPI (Visual Position Indicator) for visual signaling of the position of the valve plug
- when the valve is closed, the red band normally hidden by the reset knob is visible
- equipped with a button for manual closing of the solenoid valve, which can be used as a replacement element for a manually closing tap

Technical Features

USE	NOT AGGRESSIVE GASES OF THE THREE FAMILIES (DRY GASES)
ROOM TEMPERATURE	- 20°C ÷ + 60°C
SUPPLY VOLTAGES	230 V 50 - 60 HZ (SINGLE-PHASE ONLY, THE APPLIANCE DOES NOT WORK IF POWERED THREE-PHASE)
ELECTRICAL WIRING	STRAIN RELIEF M20 X 1.5



Manual Reset Solenoid Valve for Gas

COIL	7 VA (8 VA 1")
ABSORBED POWER	230 V = 7/8 VA
MAXIMUM WORKING PRESSURE	500 MBAR
CLOSING TIME	< 1 S
DEGREE OF PROTECTION	IP65 (PROTECTED AGAINST JETS OF WATER PUMPED FROM ANY DIRECTION AND COMPLETELY HERMETIC AGAINST DUST AND FUMES)
MATERIALS	BODY AND BLOCK COIL IN BRASS MONOBLOCK
MECHANICAL STRENGTH	GROUP 2
CONNECTIONS	1/2" FF - 3/4" FF - 1" FF
COMPLIANCE	<ul style="list-style-type: none"> • EMC DIRECTIVE 2014/30/EU • LVD DIRECTIVE 2014/35/EU • ROHS II DIRECTIVE 2011/65/EU

SKU	MODEL	PRICE
00000050561		€77.8 VAT EXCLUDED
00000050562		€77.8 VAT EXCLUDED
00000050563		€98.6 VAT EXCLUDED



Manual Reset Solenoid Valve for Gas

