



## PERISTALTIC PUMP PE 5200

For condensate drain

### Product informations

**Peristaltic pump PE 5200** used for the discharge of condensate full of impurities and intended for applications where the quantity of condensate is modest; operated via the 3-level float detection block. Its alarm contact is normally closed, and allows the air conditioning compressor or a solenoid valve to be automatically stopped when the safety level is reached

### Product features

- compact design
- the replaceable head and easy-to-access tube, reduce maintenance costs
- low sound level
- 3 function levels - Start / Stop / Safety contact

### The kit includes

- **PE 5200** peristaltic pump
- power cable: 1,7 m, 2 thread
- safety contact cable: 1,7 m, 2 thread
- sliding plastic plate, easy to assemble
- float detection block
- detection block installation kit: sleeve Ø 15 x 35 mm - breather pipe Ø int 4 x L. 75 mm - mounting guide - adhesive for fixing



## Peristaltic Pump PE 5200

### Technical Features

<b>POWER SUPPLY</b>	230 V 50 HZ 11 W
<b>MAXIMUM FLOW RATE</b>	6 L/H
<b>MAX. ASPIRATION HEIGHT</b>	2 M
<b>MAX DISCHARGE</b>	12 M
<b>SOUND LEVEL TO 1 M</b>	≤ 30 DB(A)
<b>SAFETY SWITCH</b>	NF 8 RESISTIVE - 250 V
<b>DETECTION LEVELS</b>	<ul style="list-style-type: none"> <li>• ON: 16 MM</li> <li>• OFF: 11 MM</li> <li>• SAFETY: 19 MM</li> </ul>
<b>DEGREE OF PROTECTION</b>	IP65 (COMPLETELY HERMETIC AGAINST DUST AND FUMES, PROTECTED AGAINST JETS OF WATER FROM ANY DIRECTION)
<b>PUMP BLOCK DIMENSIONS</b>	109 X 110 X 91 MM (LXDXH)
<b>DETECTION BLOCK SIZE</b>	55 X 38 X 37,5 MM (LXDXH)

SKU	MODEL	PRICE
00000011916	PERISTALTIC PUMP PE 5200	€419.34 VAT EXCLUDED





## Peristaltic Pump PE 5200

