



Catalogues and Products > Air-Conditioning > FastPipe® > **Tube Coil with UV-PRO Coating**

TUBE COIL WITH UV-PRO COATING

Component of the FastPipe® SYSTEM

Product informations

The heart of **FastPipe® SYSTEM** is the pipe, available in different configurations with which it is possible to best design and customize a system.

The coiled tube is available in different configurations

- without coating (50 m coils)
- with 6 mm white coating
- with 6 mm UV-Pro coating (grey)

The hose also complies with the following regulations

- Global compliance with regulations: **UNI EN 1736:2009 (EN 1736:2008)**
- Coating (thermal conductivity): **UNI 8457 - UNI 9174**
- Coating (fire resistance): **UNI EN 1382:2014 - UL 94:2001**
- Resistance to permeation: **EN 1736 Top Performer Classe 1**

What is UV-PRO?

It is a pearly grey coating that is resistant to UV rays and the aggression of sunlight 3 times more than common polyethylene film. This type of coating preserves both the pipe and the insulating coating and is therefore able to guarantee excellent performance of the air conditioning system.



Tube Coil with UV-PRO Coating

In any case, remember to refer to the instruction manual on correct practices for protecting the pipes from direct exposure to sunlight.

Technical Features

COMPATIBLE GASES	R407C - R410A - R32 - TR422B - R134A - R404 (NOT COMPATIBLE WITH R22 GAS)
OPERATING TEMPERATURE	- 30°C ÷ + 110°C (ALSO WITHSTANDS NON-CONTINUOUS 130°C SPIKES)
MAXIMUM OPERATING PRESSURE	60 BAR

MINIMUM BENDING RADIUS			
1/4"	3/8"	1/2"	5/8"
65 MM	95 MM	130 MM	170 MM

TIGHTENING TORQUE			
1/4"	3/8"	1/2"	5/8"
15-17 NM (MAX. 20 NM)	28-32 NM (MAX. 35 NM)	38-42 NM (MAX. 45 NM)	60-68 NM (MAX. 80 NM)

SKU	MODEL	PRICE
00000013060		€304.0 VAT EXCLUDED
00000013061		€435.8 VAT EXCLUDED
00000013062		€668.35 VAT EXCLUDED
00000013063		€1048.35 VAT EXCLUDED



Tube Coil with UV-PRO Coating

