



## PURE NEUTRAL SILICONE

High elasticity pure neutral silicone

### Product informations

Pure neutral silicone with characteristics of high elasticity, adhesion and resistance to high and low temperatures; once hardened, the product forms an elastic and resistant material, ideal for professional sealing and assembly applications. Suitable for materials such as glass, ceramic, wood, metal surfaces (not oxidized), plastic surfaces (excluding PE, PP, PTFE), anodized aluminum, polycarbonate, mirrors, building materials and concrete.

### Product features

- not paintable
- not corrosive
- slight odor, suitable for application in closed environments
- excellent elasticity and adhesion
- resistance to UV rays, chemicals, abrasion and wear
- ANTI-MOLD
- excellent adhesion on water-based paints

### Technical Features

<i>DENSITY</i>	1.015 G/CM <sup>3</sup>
<i>WORKABILITY TIME</i>	8 MINUTES
<i>TIME FOR "PEEL MAKING"</i>	15 MINUTES



**Pure Neutral Silicone**

<b>"HARDENING" TIME (3 MM LAYER)</b>	24 HOURS
<b>HARDNESS</b>	20
<b>CONTENT</b>	310 ML
<b>CONSERVATION</b>	13 MONTHS IN A DRY PLACE AT A TEMPERATURE BETWEEN 5°C AND 25°C
<b>RESISTANCE TO TEMPERATURE</b>	- 20°C ÷ + 100°C

SKU	MODEL	PRICE
00000050932	TRANSPARENT NEUTRAL SILICONE - 310 ML	€11.3 VAT EXCLUDED
00000050933	NEUTRAL SILICONE DARK BROWN - 310 ML	€13.8 VAT EXCLUDED

