



## Recovery Station TGAS-REC-24 COMPACT - 1 HP, with Separation

Catalogues and Products > Condizionamento > Attrezzature per Vuoto e Carico > **Recovery Station TGAS-REC-24 COMPACT - 1 HP, with Separation**

# RECOVERY STATION TGAS-REC-24 COMPACT - 1 HP, WITH SEPARATION

Recovery station TGAS-REC-24 COMPACT model 1 HP, with 3 taps and separation of oil and filter

## Product informations

System for the recovery of refrigerant gas from the refrigerant circuit and subsequent storage in a pressurized container to avoid dispersion into the atmosphere (*as per current legislation Art n°6 Law 549/93 and Art. N°16 European Reg 2037/00*). The recovery unit is equipped with two dry pressure gauges, one on the suction line and one on the discharge line, which allow the control of pressures during the recovery and transfer of the refrigerant with the *PUSH-PULL* method. The station is also equipped with an oil separator and filter. Finally, the presence of a single selector for the various functions of the recuperator will make your work easier and safer. Thanks to the small size and the central positioning of the handle, the transport of the recovery station will be easier.

***Suitable for all types of CFC-HCFC-HFC refrigerant gases.***








## Technical Features

<b>COMPRESSOR</b>	OIL LESS MAINTENANCE FREE
<b>POWER SUPPLY</b>	230 V - 50 HZ (1450 RPM)
<b>POWER</b>	1 HP - 750 W
<b>SAFETY</b>	AUTOMATIC SHUT-DOWN WITH PRESSURE HIGHER THAN 38,5 BAR
<b>WEIGHT</b>	14,7 KG



## Recovery Station TGAS-REC-24 COMPACT - 1 HP, with Separation

<b>DIMENSIONS</b>	450 X 250 X 355 MM (L X P X H)
<b>RECOVERY RATE</b>	<ul style="list-style-type: none"> <li>• VAPOUR RATE UP TO 30 KG/H</li> <li>• LIQUID RATE UP TO 210 KG/H</li> <li>• PUSH-PULL RATE UP TO 570 KG/H</li> </ul>

SKU	MODEL	PRICE
		
		
		



## Recovery Station TGAS-REC-24 COMPACT - 1 HP, with Separation

