



Catalogues and Products > Heating > High and Low Pressure Lpg Regulators for Civil-industrial Applications >

Low Pressure Regulator with Manual Reset

LOW PRESSURE REGULATOR WITH MANUAL RESET

Model with maximum pressure block only valve and relief incorporated, flow rate 3 and/or 4 kg

Product informations

Low pressure regulator with manual reset for LPG with maximum pressure block only valve (OPSO) and relief valve incorporated, designed to make the gas pressure at the outlet of a tank suitable for the downstream user.

The regulator supplied with

- fixing support
- security seal
- nut and injector (to be installed)

Technical Features


| | |
|------------------------------|---|
| TYPES OF GAS | LPG |
| FLOW RATE | <ul style="list-style-type: none">• 3 KG - SKU 1689• 4 KG - SKU 1690 |
| OPERATING TEMPERATURE | - 20°C ÷ + 50°C |



Low Pressure Regulator with Manual Reset

| | |
|------------------------|--|
| INLET PRESSURE | 0,3 ÷ 16 BAR |
| OUTLET PRESSURE | <ul style="list-style-type: none"> • 37 MBAR - SKU 1689 • 29 MBAR - SKU 1690 |
| CONNECTIONS | IN NUT W20LH-25-UNI OUT 1/2" F |
| MATERIALS | <ul style="list-style-type: none"> • BODY AND COVER: ZINC ALLOY (ZAMA) • DIAPHRAGM AND GASKETS: ELASTOMER COMPLIANT WITH EN549 |

| SKU | MODEL | PRICE |
|-------------|-------|----------------------|
| 00000001689 | | €133.4 VAT EXCLUDED |
| 00000001690 | | €136.05 VAT EXCLUDED |





Low Pressure Regulator with Manual Reset

