



Catalogues and Products > Riscaldamento > Regolatori Gpl Alta e Bassa Pressione per Applicazioni Civili-industriali > **First Stage Regulator Mod. APS2000**

FIRST STAGE REGULATOR MOD. APS2000

Model with external setting, flow rate 150 kg/h

Product informations

First stage high pressure regulator **Mod. APS2000**, designed to be connected directly to the tank or cylinder, reducing the pressure down to an intermediate pressure towards a second stage regulator.

Also available in the version with 2 dry pressure gauges (sku 2530) or in glycerine bath (sku 2540).

Technical Features

TYPES OF GAS	LPG
FLOW RATE	150 KG/H
OPERATING TEMPERATURE	- 20°C ÷ + 50°C
INLET PRESSURE	0,5 ÷ 16 BAR
OUTLET PRESSURE	0,5 ÷ 2 BAR - EXTERNAL SETTING
PRESSURE GAUGES SKU 2530	<ul style="list-style-type: none"> • RADIAL CONNECTION 1/4" - 0 ÷ 4 BAR - Ø 63 - DRY • RADIAL CONNECTION 1/4" - 0 ÷ 16 BAR - Ø 63 - DRY
PRESSURE GAUGES SKU 2540	<ul style="list-style-type: none"> • RADIAL CONNECTION 1/4" - 0 ÷ 4 BAR - Ø 63 - GLYCERIN BATH • RADIAL CONNECTION 1/4" - 0 ÷ 25 BAR - Ø 63 - GLYCERIN BATH
CONNECTIONS	IN 3/4" F - OUT 3/4" F



First Stage Regulator Mod. APS2000

MATERIALS	<ul style="list-style-type: none"> • BODY AND COVER: ALUMINUM ALLOY • DIAPHRAGM AND SHUTTER: LPG RESISTANT SYNTHETIC RUBBER
------------------	---

SKU	MODEL	PRICE
00000002500	REGULATOR MOD. APS2000 - IN 3/4" F - OUT 3/4" F - FLOW RATE 150 KG/H - EXTERNAL SETTING	€298.2 VAT EXCLUDED
00000002530	REGULATOR MOD. APS2000 WITH DRY PRESSURE GAUGES - IN 3/4" F - OUT 3/4" F - FLOW RATE 150 KG/H - EXTERNAL SETTING	€326.9 VAT EXCLUDED
00000002540	REGULATOR MOD. APS2000 WITH GLYCERINE BATH PRESSURE GAUGES - IN 3/4" F - OUT 3/4" F - FLOW RATE 150 KG/H - EXTERNAL SETTING	€339.8 VAT EXCLUDED

