



## LOW PRESSURE REGULATOR

Model DIVAL 507 and 512

### Product informations

Low pressure regulator Mod. DIVAL 507 and 512 equipped with incorporated safety relief valve and internal sensing line, to be used with previously filtered not corrosive gases.

**Also available in the version with shut-off valve for maximum and minimum downstream pressure (sku 1210B / 1220B).**

### Technical Features

SKU	MODEL	FLOW RATE	CONNECTIONS	VENT VALVE DIAMETER	INLET PRESSURE	OUTPUT PRESSURE RANGE	STANDARD PRESSURE	ROOM TEMPERATURE	MATERIALS	DIMENSIONS
1210	DIVAL 507	60 KG/H - 50 M <sup>3</sup> /H	IN 1" F - OUT 1" F	Ø 1/4" F	0,5 ÷ 5 BAR	15 ÷ 110 MBAR	20 ÷ 30 MBAR	- 20°C ÷ + 50°C	<ul style="list-style-type: none"> <li>• BODY: GS 400 CAST IRON</li> <li>• HEADER: ALUMINUM</li> <li>• SEAT: BRASS</li> <li>• MEMBRANE: RUBBER WITH FABRIC FINISH</li> <li>• O-RING: NITRILE RUBBER</li> </ul>	100 X 190 X 49 X 185,5 MM (AXBXCXD)
1210B	DIVAL 507 WITH SHUT-OFF VALVE	60 KG/H - 50 M <sup>3</sup> /H								100 X 190 X 185 X 185,5 MM (AXBXCXD)
1220	DIVAL 512	120 KG/H - 100 M <sup>3</sup> /H	IN 1" F - OUT 1" 1/2 F							129 X 257 X 55 X 185,5 MM (AXBXCXD)
1220B	DIVAL 512 WITH SHUT-OFF VALVE	120 KG/H - 100 M <sup>3</sup> /H								129 X 194 X 185 X 185,5 MM (AXBXCXD)



## Low Pressure Regulator

SKU	MODEL	PRICE
00000001210		ON REQUEST
00000001220		ON REQUEST
0000001210B		ON REQUEST
0000001220B		ON REQUEST





## Low Pressure Regulator

