



Catalogues and Products > Riscaldamento > Regolatori Metano/gpl per Applicazioni Civili - Industriali > **Medium Pressure Regulator**

MEDIUM PRESSURE REGULATOR

Alfa 60 MP series, with balanced direct action regulation

Product informations

Alfa 60 MP series regulator with balanced direct action, equipped with internal sensing line, suitable for the use of not corrosive gases as methane and LPG.

Also available the version with minimum and maximum pressure shut-off valve downstream (sku 2622).

Technical Features

FLOW RATE	SEE TABLE UNDERLYING
INLET CONNECTION	DN 50
OUTPUT CONNECTION	DN 50
INLET PRESSURE	0,5 ÷ 5 BAR
OUTPUT PRESSURE	0,2 ÷ 1 BAR
STANDARD OUTPUT PRESSURE	ON REQUEST
WORKING TEMPERATURE	- 20°C ÷ + 60°C
EXTERNAL SENSING LINE	Ø 14



Medium Pressure Regulator

MATERIALS	<ul style="list-style-type: none"> • BODY: GS 400 CAST IRON • HEADER: STEEL • SEAL: NITRILE RUBBER NBR OR HNBR • MEMBRANE: SANDWICH RUBBERIZED FABRIC
DIMENSIONS	540 X 254 X 110 MM

FLOW RATE TABLE M³/H

INLET PRESSURE

	0,5 BAR	1 BAR	1,5 BAR
0,2 BAR	826 M ³ /H	1375 M ³ /H	1812 M ³ /H
0,3 BAR	702 M ³ /H	1328 M ³ /H	1788 M ³ /H
OUTLET PRESSURE			
0,5 BAR	-	1194 M ³ /H	1719 M ³ /H
0,7 BAR	-	983 M ³ /H	1617 M ³ /H
1 BAR	-	-	1376 M ³ /H

To obtain the LPG flow rates in kg/h, multiply the values in red by 1.42.

SKU	MODEL	PRICE
00000002620	ALFA 60 MP SERIES REGULATOR - DN 50 - DN 50 CONNECTION	€4750.0 VAT EXCLUDED
00000002622	ALFA 60 BP SERIES REGULATOR - DN 50 - DN 50 CONNECTION - WITH BLOCK	€6004.0 VAT EXCLUDED



Medium Pressure Regulator

