



Catalogues and Products > Riscaldamento > Blue Kit Linea Tecnoblue > **Standard Blue Kit**

## STANDARD BLUE KIT

The complete boiler-saver kit

### Product informations

**BLUE KIT STANDARD** consists of the *MagBlue Mini* magnetic filter (SKU 70045), the *DosaBlue One* polyphosphate dispenser (SKU 70874), the Neutral Acid Water 35K neutralizing cartridge and the *LiquidBlue 100* anti-scaling anticorrosive liquid (SKU 70085).

### Technical Features

SKU 70045	
MAXIMUM WORKING PRESSURE	10 BAR
WORKING TEMPERATURE	0 ÷ 90°C
LOAD LOSS	0,2 BAR
MAXIMUM HOURLY FLOW	1,3 M <sup>3</sup> /H
MAGNETIC FLUX DENSITY	12800 GAUSS
FILTRATION DEGREE	300 - 800 μM
MAGNET	NEODIMIO
CONNECTIONS	3/4"


**Standard Blue Kit**

<i>SKU 70874</i>	
<i>90° CONNECTIONS</i>	<i>IN/OUT 1/2" MOBILE</i>
<i>MAX FLOW RATE</i>	<i>1,5 M<sup>3</sup>/H</i>
<i>MAX PRESSURE</i>	<i>3,5 BAR</i>
<i>WORKING TEMPERATURE</i>	<i>0°C - 45°C</i>
<i>RECHARGE AUTONOMY</i>	<i>12 - 15 M<sup>3</sup></i>
<i>PRESSURE DROP</i>	<i>0,2 BAR</i>
<i>VASE MATERIAL</i>	<i>SAN</i>

<i>SKU 70894</i>	
<i>VALID FOR BOILERS UP TO 35 KW</i>	
<i>LENGTH</i>	<i>220 MM</i>
<i>DIAMETER</i>	<i>47 MM</i>
<i>MAX PRESSURE</i>	<i>0,5 BAR</i>
<i>MAXIMUM TEMPERATURE</i>	<i>60°C</i>
<i>MAX CAPACITY</i>	<i>8 L/H</i>
<i>UNIT MATERIAL</i>	<i>PP</i>
<i>HOSE HOLDER MATERIAL</i>	<i>PP</i>
<i>MATERIAL FIXING SYSTEM</i>	<i>PP</i>
<i>NEUTRALIZING CHARGE IN CALCIUM CARBONATE (CaCO<sub>3</sub>)</i>	
<i>EPDM HYDRAULIC SEALS</i>	



**Standard Blue Kit**

<b>SKU 70894</b>	
<b>ACCESSORIES</b>	<ul style="list-style-type: none"> <li>• PAIR OF 3/4" STRAIGHT HOSE CONNECTORS</li> <li>• FIXING CLIP WITH Ø 50 MM SCREWS</li> </ul>

<b>SKU 70085</b>	
<b>CATEGORY</b>	AUXILIARY CHEMICAL PRODUCT FOR WATER TREATMENT
<b>APPLICATION</b>	BIOCIDAL ANTI-CORROSION ANTISCALANT FOR CLOSED CIRCUITS
<b>APPEARANCE</b>	LIQUID
<b>COLOR</b>	AMBER
<b>PH</b>	6,8
<b>RELATIVE DENSITY</b>	1,06
<b>WORKING TEMPERATURE</b>	FROM 10°C TO 130°C
<b>SOLUBILITY WATER</b>	SOLUBILE
<b>WATER COMPATIBILITY</b>	<ul style="list-style-type: none"> <li>• MAKE-UP WATERS WITH LIMITED HARDNESS LEAKS</li> <li>• MEDIUM HARD WATER</li> <li>• SOFTENED OR DEMINERALISED WATER</li> </ul>
<b>DOSAGE</b>	IT CAN BE INTRODUCED INTO THE SYSTEM VIA THE DOSING PUMP, FEED TANK OR OTHER CONVENIENT POINT IN THE CIRCUIT. THE OPTIMAL DOSAGE FOR CORRECT SYSTEM PROTECTION IS <u>1 LITER FOR EVERY 100 LITERS OF WATER IN THE HEATING SYSTEM.</u>
<b>1 L JUG (1 KG)</b>	



## Standard Blue Kit

SKU	MODEL	PRICE
00000070078	STANDARD BLUE KIT	€168.45 VAT EXCLUDED

