



Catalogues and Products > Air-Conditioning > Fittings in Copper and Brass > **Steel Filters**

STEEL FILTERS

With threaded connections

Product informations

Bidirectional dehydrating filters, equipped with a solid cartridge made of 100% molecular sieve; the *TGAS - MG BI-FLOW* steel filters for heat pumps are specifically designed for both refrigeration and air conditioning systems.

Product features

- equipped with a nickel-plated steel body
- salt fog corrosion resistance 500 hours

Technical Features

SKU	TYPE OF REFRIGERANTS	NOMINAL VOLUME (CM ³)	WORKING PRESSURE	MWP (PSI)	TS (°C)		CONNECTIONS	DIMENSIONS		WEIGHT
					MIN	MAX		Ø D	LENGTH	



Steel Filters

11983	<ul style="list-style-type: none"> • HCFC (R22) • HFC (R134A - R404A - R407C - R410A - R507) 	80 CM ³						1/4" SAE M.M.	121 MM	480 G	
11985	<ul style="list-style-type: none"> • HFO (R1234ZE) • HFO + HFC (R448A - R449A - R450A - R452A - R513A - R515A - R515B) 	130 CM ³	45 BAR	680 PSI	- 40°C	+ 80°C		3/8" SAE M.M.	64 MM	152 MM	600 G
11986	<ul style="list-style-type: none"> • HC (R290 - R600 - R600A - R1270) 	130 CM ³						1/2" SAE M.M.		157 MM	630 G

SKU	MODEL	PRICE
00000011983	FILTERS 1/4" SAE M.M.	€23.9 VAT EXCLUDED
00000011985	FILTERS 3/8" SAE M.M.	€31.7 VAT EXCLUDED
00000011986	FILTERS 1/2" SAE M.M.	€33.65 VAT EXCLUDED

