



Catalogues and Products > Air-Conditioning > Condensate Discharge Accessories > **TECNOSLIM Pump**

TECNOSLIM PUMP

Small, thin and silent

Product informations

TECNOSLIM pump, small, thin and silent; also suitable for air conditioners with cooling capacity, it is supplied complete with installation accessories.

N°	DESCRIPTION
1	PUMP MAIN UNIT
2	INTERNAL DIAMETER CRYSTAL PIPE Ø 6 MM
3A	TANK CAP AND SENSOR CABLE
3B	FLOAT
3C	RESERVOID FILTER
3D	RESERVOID
4	CRYSTAL PIPE INTERNAL DIAMETER Ø 6 MM OF 1,5 M
5	CONDENSATE INLET PIPE
6	POWER CABLE
7	2 SELF-ADHESIVE VELCRO STRIPS
8	4 CABLE TIES 200 MM X 5 MM
TO COMPLETE THE INSTALLATION, YOU WILL NEED SEVERAL METERS OF CRYSTAL PVC PIPE Ø 6X9 MM	



TECNOSLIM Pump

Technical Features

MAXIMUM FLOW RATE	15 L/H (DISCHARGE LENGHT 0 M)
POWER SUPPLY	230 V 50-60 HZ
MAX SPLIT POWER	16 KW - 54600 BTU/H
MAXIMUM SUCTION LIFT	2 M
MAXIMUM PUSH HEIGHT	12 M
TANK CAPACITY	40 CC
PUMP DIMENSIONS	112X29X29 MM (LXDXH)
DISCHARGE TUBE DIMENSIONS	<ul style="list-style-type: none"> • Ø INTERNAL: 6 MM • Ø EXTERNAL: 9 MM
MAXIMUM WATER TEMPERATURE	40°C
SOUND LEVEL	19DB (A) 1 M
SAFETY SWITCH	3A NORMALLY CLOSED
DEGREE OF PROTECTION	IPX5 (ENCLOSURE PROTECTED AGAINST JETS OF WATER PUMPED FROM ANY DIRECTION)
THERMAL INSULATION CLASS	II

SKU	MODEL	PRICE
00000011944	TECNOSLIM PUMP	€150.25 VAT EXCLUDED





TECNOSLIM Pump

