



Catalogues and Products > Riscaldamento > Vaporizzatori per Gpl > **LPG Water Vaporizer**

LPG WATER VAPORIZER

Feed-Out type, flow rate 100 and/or 200 kg/h

Product informations

Water LPG vaporizer *mod. Feed-Out*, designed to transform liquefied gas at the inlet, to a gaseous state at the outlet in maximum safety, ready to be used in civil, industrial and commercial systems; this vaporizer works in open cycle with the powered system, equipped with mechanical control of the liquid level inside and with the possibility of liquid return to the tank in case of overpressure.

Vaporizer equipped with

- pressure gauge
- safety valve
- thermometer
- filter
- ball valve
- water safety valve
- vent release valve

Technical Features

GAS INLET	DN 15
GAS OUTLET	DN 25
WATER INLET	Ø 1"



LPG Water Vaporizer

WATER OUTLET	Ø 1"
PRESSURE GAUGE	Ø 60 MM - SETTING 25 BAR
SAFETY VALVE	Ø 1/2" - SETTING 18 BAR
THERMOMETER	- 20°C ÷ + 120°C
BALL VALVE	DN 15 - PN 40
WATER SAFETY VALVE SETTING	1,5 BAR
PROJECT TEMPERATURE	- 40°C ÷ + 120°C
PROJECT PRESSURE	40 BAR
FLOW RATE	<ul style="list-style-type: none"> • 100 KG/H - SKU 50097 • 200 KG/H - SKU 50098

DIMENSIONS					
SKU	A	B	C	D	E
50097	1330 MM	560 MM	420 MM	150 MM	300 MM
50098	1330 MM	560 MM	420 MM	150 MM	300 MM

SKU	MODEL	PRICE
00000050097	WATER LPG VAPORIZER FEED-OUT MODEL - FLOW RATE 100 KG/H	€3525.0 VAT EXCLUDED
00000050098	WATER LPG VAPORIZER FEED-OUT MODEL - FLOW RATE 200 KG/H	€3941.0 VAT EXCLUDED



LPG Water Vaporizer

